

New Tools for AFC3000 **CFT-051RS1-S/SL** **NEW !**



Max. Speed 1330rpm
(260% UP)

Minimizing the effect of external force on torque accuracy by integrating a torque transducer into the tool

Available in the same mounting dimensions as our existing products NFT-051RM1-S /-S1

*CFT-051RS1-S

Tool specifications

Straight tool

NEW

Model	Torque Range [Nm]	Max. Speed [rpm]	Weight [kg]	Square Drive [mm](inch)
MFT-080M10-S1	0.8	1660	0.66	Hex. 6.35 (1/4)
MFT-240M10-S	2.4	600	0.68	Hex. 6.35 (1/4)
CFT-051RS1-S	5.0	1330	1.16	□9.5 (3/8)
CFT-101RS1-S	10.0	3000	1.26	□9.5 (3/8)
CFT-201RS1-S	20.0	1293	1.42	□9.5 (3/8)
CFT-281RS1-S	28.0	992	1.42	□9.5 (3/8)
CFT-401RS1-S	40.0	712	1.42	□9.5 (3/8)
CFT-801RS3-S	80.0	1015	3.4	□12.7 (1/2)
CFT-132RS3-S1	130.0	574	3.4	□12.7 (1/2)
CFT-202RS3-S	202.0	387	4.3	□15.9 (5/8)
CFT-302RS3-S	300.0	260	5.8	□19.0 (3/4)

NOTE) Specifications and designs of the products are subject to change without notice due to improvements.



<https://www.daiichi-dentsu.co.jp>
sales@daiichi-dentsu.co.jp

Head office: 1-54-1, Shimoishihara, Chofu-City,
 Tokyo 182-0034, Japan
 Phone: 81-42-440-1465
 Fax: 81-42-440-1436

Kani Plant: 690-1, Omori, Kani-City,
 Gifu, 509-0238, Japan
 Phone: 81-574-62-5865
 FAX: 81-574-62-3523